HONGKONG KOON TECHNOLOGY LTD
1001 T3 Uni Business Center Baoan Shenzhen China 518101
Tel: 0086755 27448753 Email: mrkt47@koontech.com
Web: www.koontech.com

Visual Beacon D7



Application:
Widely used in oil exploration, refining, chemical, military, and other hazardous environments and offshore oil platforms, oil tankers and other places for general lighting and task lighting purposes;
Suitable for energy-saving projects and repair and replacement places;
Suitable for higher protection requirements, moist places;
Suitable for explosive gas atmospheres of Zone 1, Zone 2 locations;
Applicable Ⅱ Class C explosive gas atmospheres; Suitable for temperature class T6

Features:
Aluminum die-cast shell, surface electrostatic spray.
Glass shade, with a strong impact resistance.
High corrosion resistance of stainless steel exposed fasteners;
LED light source, high brightness, long service life.
Pipe or cable wiring.

HONGKONG KOON TECHNOLOGY LTD
1001 T3 Uni Business Center Baoan Shenzhen China 518101
Tel: 0086755 27448753 Email: mrkt47@koontech.com
Web: www.koontech.com

Technical Specification

Model: D7
Hot Line Standard: GB3836.1, GB3836.2, GB3836.4, GB12476.1, IEC60079-0, IEC60079-1, IEC60079-11, IEC61241-0, IEC61241-1, EN60079-1, EN60079-11, EN61241-0, EN61241-1
Ex-mark: Exd II CT6 Gb/Ex tD A21 IP65 T80℃
Rated voltage: AC110~230V 50Hz (if any special requirements please specify) Protection class: IP65
Corrosion grade: WF1 * WF2
Flash Views: 150 times / min
Intakes specifications: G3 / 4 ", suitable for Φ10mm ~ Φ14mm cable
Terminals: ≤ 2.5mm ²
Installation: pedestal (z)
Product Weight: 2.5kg

Dimension (mm)

